

Juniper Networks QDD-400G-AOC-10M
Compatible 400G QSFP-DD AOC
(10-meter, QSFP-DD to QSFP-DD)




Product Specifications

Form Factor QSFP-DD to QSFP-DD	Data Rate 400Gbps
Cable Length 10m (33ft)	Cable Type OM4
Wavelength 850nm	Minimum Bend Radius 30mm
Transmitter Type VSCEL	Receiver Type 850nm PD
Power Consumption ≤11W	Jacket Material LSZH
CDR (Clock and Data Recovery) TX & RX Built-in CDR	Modulation Format PAM4
DDM/DOM Yes	Commercial Temperature 0 to 70°C
Protocols IEEE 802.3cd, OIF-CEI-04.0, QSFP-DD MSA, QSFP-DD-CMIS-rev4p0	Inbuilt FEC No
Application 8x 50G-PAM4	Juniper Compatible QDD-400G-AOC-10M



Contact Us:
Email: sales@compufox.com

 (305) 865-8517  +1 (305) 710-6768



Compatible Devices:

- Juniper ACX7100-32C
- Juniper ACX7100-48L
- Juniper ACX7509
- Juniper MX304
- Juniper PTX10001-36MR
- Juniper PTX10004
- Juniper PTX10008
- Juniper PTX10016
- Juniper QFX5130-32CD
- Juniper QFX5220-32CD
- Juniper QFX5230-64CD
- Juniper QFX5700

Supported Interface Modules:

- ACX7509-FPC-4CD (ACX7509)
- MX304-LMIC16 (MX304)
- PTX10K-LC1201-36CD (PTX10004, PTX10008, PTX10016)
- QFX5K-FPC-4CD (QFX5700)

Contact Us:

Email: sales@compufox.com

 (305) 865-8517  +1 (305) 710-6768

