

External Mini SAS SFF-8088 to Mini SAS SFF-8088 6G SAS Cable.

This External 26-pin Mini-SAS to Mini-SAS (SFF-8088 to SFF-8088) Cables maximize SAS drive and storage array performance with SKEWCLEAR cable technology. Spectra-Strip SKEWCLEAR shielded parallel-pair wire guarantees sustained data-rates up to 6.0 Gbps per lane, reduced signal loss and improved cross-talk performance.

This 4x Mini-SAS cable features universal keyed 26-pin SFF-8088 pull to release connectors. The lanyard disconnect pull-to-release connector is compatible with all mini-SAS ports.

Thinner and more flexible than competing SAS products, our cables offer convenient routing options and improved airflow for your datacenter.



Features

- Guaranteed SAS-II drive performance at 3.0 Gbps & 6.0 Gbps data rates
- SFF-8088 (26-pin Mini-SAS) to SFF-8088 (26-pin Mini-SAS) connectors
- Universal key (2, 4, 6) Mini-SAS connectors with pull-to-release lanyard
- 4X Twinaxial SKEWCLEAR 8-pair high-bandwidth low-skew cable
- Ideal external cabling solution for connecting two Mini-SAS devices
- Fully compliant to the latest SAS 2.0 interface specifications
- Subject to Serial Attached SCSI test certification before shipment
- Available in lengths ranging from 0.5m to 7m
- RoHS compliant cable design meets environmental standards



SFF-8088



Specifications

- Cable Type: External 26-pin 4x Mini-SAS Cable
- Connector A: SFF-8088 (26-pin Mini-SAS)
- Connector B: SFF-8088 (26-pin Mini-SAS)
- Cable Length: 0.5m
- Data Rate: 6Gbps
- Number of Channels: 4x
- Wire Size: 30AWG
- Product Types: Passive
- Compliance/Standards: SAS 2.1
- Operating Temperature Range: -40°C to 85°C
- Packaging: Anti-Static Bag