

QDD-4X100G-FR

Part number: 740-085354

Optics Overview

Juniper Networks offers a complete portfolio of modular and fixed-chassis routers and switches for both WAN and data center networks. These solutions span Juniper’s MX-Series Universal Routing Platform and PTX-Series Packet Transport Routers to EX-Series Ethernet Switches and QFX-Series Data Center Switches among others. Depending on deployment scenarios, Juniper’s platforms support different pluggable optic modules that can be selected based on speed, distance, form-factor, and wavelength among other relevant attributes.

Additional Resources

Hardware Compatibility Tool

HCT contains a regularly updated database of Juniper’s transceivers, DACs, and AOCs along with information regarding compatibility with Juniper’s platforms and interface modules.

<https://apps.juniper.net/hct/home/>

Product Description

QSFP-DD 4x100G-FR, SMF 2 km; Standard Temperature (0 through 70°C); MPO-12 APC Receptacle

Overview

Part Number	740-085354
Speed	4 x 100 Gigabit Ethernet, 400 Gigabit Ethernet
Breakout Capable	Yes
Transceiver Type	QSFP-DD
Product Type	Optical Transceiver
Connector	MPO-12 APC
Monitoring Available	Yes
Digital Optical Monitoring	Yes

Note:

- Monitoring Available - Can measure received optical power and display in CLI.
- Digital Optical Monitoring - Full support for SFF-8636.
- Common Optic - The common optics product line provides competitively priced single-SKU optics offerings for use across Juniper routing, switching, and security platforms.

Specifications

Standard: 100G-FR, 100GBASE-FR1, 100GBASE-DR and 400GBASE-DR4

Standards compliance (Ethernet/OTN Standard, for e.g. 100GBASE-LR4)	100G Lambda MSA, 100G-FR IEEE P802.3cu, 100GBASE-FR1 IEEE Std 802.3cd-2018, 100GBASE-DR IEEE Std 802.3-2018, 400GBASE-DR4
MSA compliance (SFF, for e.g. SFF-8665)	QSFP-DD MSA, QSFP-DD Hardware Specification for QSFP DOUBLE DENSITY 8X PLUGGABLE TRANSCEIVER Common Management Interface Specification (CMIS) for 8X/16X PLUGGABLE TRANSCEIVERS, Rev 3.0, September 18, 2018
Digital Diagnostic Monitoring	Transceiver Temperature Transceiver Supply Voltage Tx Bias Current Tx output power Rx received optical power
Supported applications	100G-FR/100GBASE-FR1 (CI 140), SMF 2 km 100GBASE-DR (CI 140), SMF 500 m 400GBASE-DR4 (CI 124), SMF 500 m
Signaling rate, each lane	Host lane: PAM4; 26.5625 GBd \pm 100 ppm Media lane: PAM4; 53.125 GBd \pm 100 ppm
Transmitter fibers	4
Transmitter wavelengths (range)	1304.5 nm to 1317.5 nm
Receive lane wavelengths (range)	1304.5 nm to 1317.5 nm
Transmitter output power, each lane (minimum)	-2.4 dBm
Transmitter output power, each lane (maximum)	4 dBm
Transmitter and dispersion eye closure for PAM4 (TDECQ), each lane (maximum)	3.4 dB
Receiver input power, each lane (minimum)	-6.9 dBm
Receiver input power, each lane (maximum)	4.5 dBm
Receiver sensitivity (OMA), each lane (maximum)	max (-4.5, SECQ -5.9) dBm
Stressed receiver sensitivity (OMA) each lane (maximum)	-2.5 dBm
Cable type	SMF

QDD-4X100G-FR

Core size/cladding	9/125 μm
Distance	2 km
Maximum Power consumption (W)	12 W
Operating Temperature (range)	0° C to 70° C
Storage temperature	-40° C to 85° C
Typical Weight & Dimensions	Weight: 0.2 kg Height: 13.5 mm Width: 18.35 mm Depth: 93.26 mm

Supported Platforms

Platform	Introduced Release	Additional Information
Routing		
ACX7100-32C Breakout Supported	Junos OS Evolved 21.2R1	
ACX7100-48L Breakout Supported	Junos OS Evolved 21.1R1	
ACX7348 Breakout Supported	Junos OS Evolved 23.4R1	
ACX7509 Breakout Supported	Junos OS Evolved 21.4R1	
MX240 Breakout Supported	Junos OS 20.4R1	
MX304 Breakout Supported	Junos OS 22.2R1	
MX480 Breakout Supported	Junos OS 20.4R1	
MX960 Breakout Supported	Junos OS 20.4R1	
MX2010 Breakout Supported	Junos OS 20.3R1	
MX2020 Breakout Supported	Junos OS 20.3R1	
MX10004 Breakout Supported	Junos OS 22.3R1	
MX10008 Breakout Supported	Junos OS 21.4R1	
PTX10001-36MR Breakout Supported	Junos OS Evolved 20.2R1	
PTX10003 Breakout Supported	Junos OS Evolved 19.4R1	
PTX10004 Breakout Supported	Junos OS Evolved 20.3R1	

Platform	Introduced Release	Additional Information
PTX10008 Breakout Supported	Junos OS Evolved 20.1R1	
PTX10016 Breakout Supported	Junos OS Evolved 21.2R2	
Switching		
QFX5130-32CD Breakout Supported	Junos OS Evolved 20.4R1	
QFX5130-48C	Contact your Juniper account team	
QFX5220-32CD Breakout Supported	Junos OS Evolved 20.2R1	
QFX5230-64CD Breakout Supported		
QFX5700 Breakout Supported	Junos OS Evolved 21.2R1	

Supported Interface Modules

Flexible PIC Concentrators (FPCs)

Name	Description	Platforms and Introduced Releases
400 Gigabit Ethernet		
QFX5K-FPC-4CD	4X400G linecard for QFX700 chassis	QFX5700 Junos OS Evolved 21.2R1 Breakout Supported
4 x 100 Gigabit Ethernet		
QFX5K-FPC-4CD	4X400G linecard for QFX700 chassis	QFX5700 Junos OS Evolved 21.2R1 Breakout Supported

Line Cards

Name	Description	Platforms and Introduced Releases	
400 Gigabit Ethernet			
ACX7509-FPC-4CD	ACX7509 4X200GE/4X400GE LINE CARD	ACX7509 Junos OS Evolved 21.4R1 Breakout Supported	
MX10K-LC9600	The MX10K-LC9600 (Model number: JNP10K-LC9600) is a fixed-configuration 24-port line card, which provides a line rate throughput of 9.6 Tbps	MX10004 Junos OS 22.3R1 Breakout Supported	MX10008 Junos OS 21.4R1 Breakout Supported
MX304-LMIC16	The MX304-LMIC16-BASE is a 16-port line card that supports maximum data throughput of 1.6 TB ingress and 1.6 TB egress	MX304 Junos OS 22.2R1 Breakout Supported	
PTX10K-LC1201-36CD	PTX10K 36 ports of 400 Gigabit Ethernet that provide 14.4-Tbps line rate processing speeds	PTX10004 Junos OS Evolved 20.3R1 Breakout Supported	PTX10008 Junos OS Evolved 20.1R1 Breakout Supported
		PTX10016 Junos OS Evolved 21.2R2 Breakout Supported	
PTX10K-LC1202-36MR	36-port line card that has thirty-two QSFP28 ports capable of supporting 100-Gbps speed, and four QSFP56-DD ports capable of supporting 400-Gbps speed	PTX10004 Junos OS Evolved 20.4R1 Breakout Supported	PTX10008 Junos OS Evolved 20.3R1 Breakout Supported
		PTX10016 Junos OS Evolved 21.2R2 Breakout Supported	

Name	Description	Platforms and Introduced Releases	
4 x 100 Gigabit Ethernet			
ACX7300-FPC-2CD4C	ACX7300-2CD4C: 4-Port (QSFP28) & 2-Ports (QSFP56-DD)	ACX7348 Junos OS Evolved 23.4R1 Breakout Supported	
ACX7509-FPC-4CD	ACX7509 4X200GE/4X400GE LINE CARD	ACX7509 Junos OS Evolved 21.4R1 Breakout Supported	
PTX10K-LC1201-36CD	PTX10K 36 ports of 400 Gigabit Ethernet that provide 14.4-Tbps line rate processing speeds	PTX10004 Junos OS Evolved 20.3R1 Breakout Supported	PTX10008 Junos OS Evolved 20.1R1 Breakout Supported
PTX10K-LC1202-36MR	36-port line card that has thirty-two QSFP28 ports capable of supporting 100-Gbps speed, and four QSFP56-DD ports capable of supporting 400-Gbps speed	PTX10004 Junos OS Evolved 20.4R1 Breakout Supported	PTX10008 Junos OS Evolved 20.3R1 Breakout Supported
		PTX10016 Junos OS Evolved 21.2R2 Breakout Supported	
		PTX10016 Junos OS Evolved 21.2R2 Breakout Supported	

Modular Port Concentrators (MPCs)

Name	Description	Platforms and Introduced Releases	
400 Gigabit Ethernet			
MPC10E-10C	MPC10E-10C-MRATE/MPC10E-10C-P-BASE, 10 x QSFP28/QSFP56-DD multirate port line card	MX240 Junos OS 20.4R1 Breakout Supported	MX480 Junos OS 20.4R1 Breakout Supported
		MX960 Junos OS 20.4R1 Breakout Supported	
MPC10E-15C	MPC10E-15C-MRATE/MPC10E-15C-P-BASE, 15 x QSFP28/QSFP56-DD multirate port line card	MX240 Junos OS 20.4R1 Breakout Supported	MX480 Junos OS 20.4R1 Breakout Supported
		MX960 Junos OS 20.4R1 Breakout Supported	
MX2K-MPC11E	The MX2K-MPC11E is a fixed-configuration Module Port Concentrator (MPC) which delivers bandwidth up to 4-Tbps per MPC slot for MX2020 and MX2010 routers.	MX2010 Junos OS 20.3R1 Breakout Supported	MX2020 Junos OS 20.3R1 Breakout Supported
4 x 100 Gigabit Ethernet			
MPC10E-10C	MPC10E-10C-MRATE/MPC10E-10C-P-BASE, 10 x QSFP28/QSFP56-DD multirate port line card	MX240 Junos OS 20.4R1 Breakout Supported	MX480 Junos OS 20.4R1 Breakout Supported
		MX960 Junos OS 20.4R1 Breakout Supported	
MPC10E-15C	MPC10E-15C-MRATE/MPC10E-15C-P-BASE, 15 x QSFP28/QSFP56-DD multirate port line card	MX240 Junos OS 20.4R1 Breakout Supported	MX480 Junos OS 20.4R1 Breakout Supported
		MX960 Junos OS 20.4R1 Breakout Supported	

Name	Description	Platforms and Introduced Releases	
MX2K-MPC11E	The MX2K-MPC11E is a fixed-configuration Module Port Concentrator (MPC) which delivers bandwidth up to 4-Tbps per MPC slot for MX2020 and MX2010 routers.	MX2010 Junos OS 20.3R1 Breakout Supported	MX2020 Junos OS 20.3R1 Breakout Supported

Why buy optics from Juniper?

There is value in choosing Juniper over 3rd party optics

✓ Full testing, validation, and JTAC support for Juniper optics

- Power, Electrical, and Management interfaces tested at the system level.
- Extended temperature and functional testing in DVT chamber using fully loaded systems.
- Full software integration into JUNOS/EVO for seamless part recognition, functionality, and telemetry.
- Latest qualification status and optics specifications published on [Hardware Compatibility Tool](#).

✓ Single-source provider for 1G to 400G on a variety of optical technologies

- Juniper's optics portfolio is maintained and constantly refreshed based on vendor availability.
- Automatic supply chain diversity and supply continuity - multiple optics suppliers fulfilled through Juniper.

✓ Rigorous evaluation of optical vendors

- Juniper ensures uniformity across all vendors by standardizing P-Specs for management, specs, and logs.
- Vendors are scored based on engineering and supply-chain analysis.
- Factory audits and critical component evaluation (Ex. Who is supplying the laser?).

Aren't 3rd party optics the same?

Optics may be a commodity, but some things are too good to be true

× Juniper does not Provide JTAC support for 3rd party optics

- JTAC will only assist with host-related issues unrelated to the use of 3rd party optics.

× Not all optics are the same - standards compliance does not guarantee quality or performance

- Third-party providers lack system-level knowledge and testing.
- No guarantee of vendor reliability or accountability.

× Newer technologies (ex. Coherent 400G ZR/ZR+) are complex and not simply plug-and-play

- Significant software integration necessary to enable full functionality, management, and telemetry.
- Use of unqualified 3rd party high-power optics can damage the host equipment.

× Third-party providers simply can't scale

- Incomplete solution offerings and fast turnaround times only for limited quantities.

Copyright © 2024, Juniper Networks, Inc. All rights reserved.

By accessing information contained in this document, you agree that:

- the information you are accessing is confidential to Juniper Networks
- you will not disclose this information to any party outside Juniper Networks
- you are authorized by Juniper Networks to access the information

The information in this document is provided "AS IS", with no warranties of any kind attached to the information. Any reliance upon the information shall be at the user's own risk. Juniper assumes no liability for the information contained in this document.