

QFX-SFP-10GE-SR

Part number: 740-021308

Optics Overview

Juniper Networks offers a complete portfolio of modular and fixed-chassis routers and switches for both WAN and data center networks. These solutions span Juniper’s MX-Series Universal Routing Platform and PTX-Series Packet Transport Routers to EX-Series Ethernet Switches and QFX-Series Data Center Switches among others. Depending on deployment scenarios, Juniper’s platforms support different pluggable optic modules that can be selected based on speed, distance, form-factor, and wavelength among other relevant attributes.

Additional Resources

Hardware Compatibility Tool

HCT contains a regularly updated database of Juniper’s transceivers, DACs, and AOCs along with information regarding compatibility with Juniper’s platforms and interface modules.

<https://apps.juniper.net/hct/home/>

Product Description

SFP+ 10GBase-SR 10 Gigabit Ethernet Optics, 850nm for up to 300m transmission on MMF

Overview

Part Number	740-021308
Speed	10 Gigabit Ethernet
Breakout Capable	No
Transceiver Type	SFP+
Product Type	Optical Transceiver
Connector	Duplex LC
Monitoring Available	Yes
Digital Optical Monitoring	Yes
Common Optic Equivalent	SFPP-10G-SR-C

Note:

- Monitoring Available - Can measure received optical power and display in CLI.
- Digital Optical Monitoring - Full support for SFF-8636.
- Common Optic - The common optics product line provides competitively priced single-SKU optics offerings for use across Juniper routing, switching, and security platforms.

Specifications

Standard: 10GBASE-SR

Standards compliance (Ethernet/OTN Standard, for e.g. 100GBASE-LR4)	IEEE 802.3ae–2002	
Digital Diagnostic Monitoring	Transceiver temperature Transceiver supply voltage TX bias current TX output power RX received optical power	
Signaling rate, each lane	9.95328 GBd +/- 20 ppm 10.3125 GBd +/- 100 ppm	
Transmitter wavelengths (range)	840 nm to 860 nm	
Receive lane wavelengths (range)	840 nm to 860 nm	
Transmitter output power, each lane (minimum)	-7.3 dBm	
Transmitter output power, each lane (maximum)	-1 dBm	
Receiver input power, each lane (minimum)	-9.9 dBm	
Receiver input power, each lane (maximum)	-1 dBm	
Optical Transmitter 3-dB spectral width (maximum)	0.45 nm	
Cable type	MMF	
Core size/cladding	62.5/125 µm	62.5/125 µm
	50/125 µm	50/125 µm
	50/125 µm	50/125 µm
Fiber grade	FDDI	OM1
	-	OM2
	OM3	OM4
Effective modal bandwidth	160 MHz x km	200 MHz x km
	400 MHz x km	500 MHz x km
	2000 MHz x km	4700 MHz x km

Distance	26 m	33 m
	66 m	82 m
	300 m	400 m
Maximum Power consumption (W)	1 W	
Operating Temperature (range)	0° C to 70° C	
Storage temperature	-40° C to 85° C	

Supported Platforms

Platform	Introduced Release	Additional Information
Routing		
ACX5000		
ACX7024	Junos OS Evolved 22.3R1	
ACX7100-32C	Junos OS Evolved 21.3R1	
ACX7100-48L	Junos OS Evolved 21.1R1	
ACX7348	Junos OS Evolved 23.4R1	
ACX7509	Junos OS Evolved 21.4R1	
MX150	Junos OS 17.3R1	
MX204	Junos OS 17.4R1	Supported natively on the SFP+ ports and with a QSA adapter on the QSFP28 ports
MX240	Junos OS 12.3R1	
MX304	Junos OS 22.2R1	
MX480	Junos OS 12.3R1	
MX960	Junos OS 12.3R1	
MX10003	Junos OS 18.3R1	Use the QSA adapter to convert a 40-Gbps port to a 10-Gbps or a 1-Gbps port.
MX10004	Junos OS 22.3R1	
MX10008	Junos OS 18.4R1	
MX10016	Junos OS 18.4R1	
PTX10001-36MR	Junos OS Evolved 21.2R1	
PTX1000	Junos OS 18.4R1	
PTX10002-60C	Junos OS 19.4R1	
PTX10008	Junos OS 18.4R1	
PTX10016	Junos OS 18.4R1	
SSR1200		
SSR1300		
SSR1400		

Platform	Introduced Release	Additional Information
SSR1500		
SDN and Orchestration		
NFX150	Junos OS 18.1R1	
NFX250	Junos OS 15.1X53-D40	
NFX350	Junos OS 19.4R1	
Security		
SRX380	Junos OS 20.1R1	
SRX650		
SRX1400		
SRX1500		
SRX1600	Junos OS 23.4R1	
SRX2300	Junos OS 23.4R1	
SRX3400		
SRX3600		
SRX4100	Junos OS 15.1X49-D65	
SRX4200	Junos OS 15.1X49-D65	
SRX4600	Junos OS 17.4R2	
SRX5400	Junos OS 12.3X48-D10	Introduced release on SRX-MIC-10XG-SFPP: 12.3X48-D10. Introduced release on SRX5K-MPC3-100G10G and SRX5K-MPC3-40G10G: 15.1X49-D10.
SRX5600	Junos OS 12.3X48-D10	Introduced release on SRX-MIC-10XG-SFPP: 12.3X48-D10. Introduced release on SRX5K-MPC3-100G10G and SRX5K-MPC3-40G10G: 15.1X49-D10.
SRX5800	Junos OS 12.3X48-D10	Introduced release on SRX-MIC-10XG-SFPP: 12.3X48-D10. Introduced release on SRX5K-MPC3-100G10G and SRX5K-MPC3-40G10G: 15.1X49-D10.
Switching		
EX2300	Junos OS 15.1X53-D50	
EX2300-C	Junos OS 15.1X53-D50	

Platform	Introduced Release	Additional Information
EX2300 Multigigabit	Junos OS 18.1R2	
EX3300	Junos OS 11.3R1	
EX3400	Junos OS 15.1X53-D50	
EX4100	Junos OS 22.2R1	
EX4100-F	Junos OS 22.2R1	
EX4100 Multigigabit	Junos OS 22.2R1	
EX4200	Junos OS 9.4R1	EX4200-24F-S and EX4200-48T-S switches—Junos OS for EX Series switches, Release 12.3R4 or later
EX4300	Junos OS 13.2X50-D10	EX4300-24T, EX4300-24P, EX4300-48T, EX4300-48T-AFI, EX4300-48P, EX4300-48T-DC, and EX4300-48T-DC-AFI switches—Junos OS for EX Series switches, Release 13.2X50-D10 or later EX4300-32F switches—Junos OS for EX Series switches, Release 13.2X51-D15 or later EX4300-24T-S, EX4300-24P-S, EX4300-32F-S, EX4300-48T-S, and EX4300-48P-S switches—Junos OS for EX Series switches, Release 13.2X51-D26 or later
EX4300 Multigigabit	Junos OS 18.2R1	
EX4400	Junos OS 21.1R1	
EX4400-48T	Junos OS 21.1R1	
EX4400-24T	Junos OS 21.1R1	
EX4400 Multigigabit	Junos OS 21.2R1	
EX4400-24X	Junos OS 23.1R1	
EX4400-48F	Junos OS 21.1R1	
EX4500	Junos OS 10.2R1	
EX4550	Junos OS 12.2R1	EX4550-32F-S switches—Junos OS for EX Series switches, Release 12.3R5 or later
EX4600		
EX4650-48Y	Junos OS 18.3R1	
EX6200	Junos OS 11.3R2	
EX8208	Junos OS 9.4R1	

Platform	Introduced Release	Additional Information
EX8216	Junos OS 9.4R1	
EX9204	Junos OS 12.3R2	
EX9208	Junos OS 12.3R2	
EX9214	Junos OS 12.3R2	
EX9251	Junos OS 18.1R1	
EX9253	Junos OS 18.3R1	
QFX3500	Junos OS 11.1R1	
QFX5100		Not available for the QFX5100-48T
QFX5110	Junos OS 15.1X53-D210	Small form-factor pluggable (SFP) and enhanced SFP (SFP+) optical transceivers used in the QFX5110-32Q are for the management ports only, whereas natively supported on QFX5110-48S.
QFX5120-32C	Junos OS 19.1R1	Supported only on the 2 native SFP+ ports
QFX5130-32CD	Junos OS Evolved 22.2R1	
QFX5130-48C	Contact your Juniper account team	
QFX5120-48Y	Junos OS 18.3R1	
QFX5120-48YM	Junos OS 20.4R1	
QFX5200-32C	Junos OS 19.4R1	
QFX5210-64C	Junos OS 18.1R1	
QFX5220-32CD	Junos OS Evolved 22.2R1	
QFX5220-128C	Junos OS Evolved 22.2R1	
QFX5230-64CD		
QFX5200-48Y	Junos OS 18.1R1	
QFX5700	Junos OS Evolved 22.1R1	
QFX10002		Only supported in the management Ethernet port
QFX10008		
QFX10016		

Supported Interface Modules

Adapters

Name	Description	Platforms and Introduced Releases	
10 Gigabit Ethernet			
MAM1Q00A-QSA	NVIDIA LinkX Optics QSA Cable Adapter 40Gbps QSFP+ to 10Gbps SFP+ / 1Gbps SFP ports. For more information regarding ordering Mellanox products, please contact Mellanox at: https://www.nvidia.com/en-us/networking/ethernet/cable-accessories/	MX204 Junos OS 18.3R1 MX10003 Junos OS 18.3R1 MX10008 Junos OS 18.4R1 PTX1000 Junos OS 18.4R1 PTX10008 Junos OS 18.4R1 EX9253 Junos OS 18.3R1 QFX5200-32C Junos OS 19.4R1	MX304 Junos OS 22.2R1 MX10004 Junos OS 22.3R1 MX10016 Junos OS 18.4R1 PTX10002-60C Junos OS 19.4R1 PTX10016 Junos OS 18.4R1 QFX5110 Junos OS 19.4R1
MAM1Q00A-QSA28	NVIDIA LinkX Optics QSA Cable Adapter 100Gbps QSFP28 to 25Gbps SFP28; Supported interface work with MAM1Q00A-QSA28 revision A6 For more information regarding ordering NVIDIA products, please contact NVIDIA at: https://www.nvidia.com/en-us/networking/ethernet/cable-accessories/	ACX7100-32C Junos OS Evolved 21.3R1	
Adapter			
MAM1Q00A-QSA	NVIDIA LinkX Optics QSA Cable Adapter 40Gbps QSFP+ to 10Gbps SFP+ / 1Gbps SFP ports. For more information regarding ordering Mellanox products, please contact Mellanox at: https://www.nvidia.com/en-us/networking/ethernet/cable-accessories/	PTX10001-36MR Junos OS Evolved 21.2R1	

Flexible PIC Concentrators (FPCs)

Name	Description	Platforms and Introduced Releases
10 Gigabit Ethernet		
QFX5K-FPC-20Y	20X50G linecard for QFX5700	QFX5700 Junos OS Evolved 22.1R1

I/O cards (IOCs)

Name	Description	Platforms and Introduced Releases
10 Gigabit Ethernet		
SRX1K-SYSIO-XGE	10-Gigabit Ethernet SYSIOC	SRX1400

Line Cards

Name	Description	Platforms and Introduced Releases	
10 Gigabit Ethernet			
ACX7300-16Y	ACX7300-16Y: 16-port, multi-rate (SFP56)	ACX7348 Junos OS Evolved 23.4R1	
ACX7509-FPC-20Y	ACX7509 20X1GE/10GE/25GE/50GE LINE CARD	ACX7509 Junos OS Evolved 21.4R1	
EX9200-2C-8XS	A line card with two 100-Gigabit Ethernet ports and eight 10-Gigabit Ethernet ports	EX9204 Junos OS 12.3R2	EX9208 Junos OS 12.3R2
EX9200-32XS	A line card with 32 10-Gigabit Ethernet ports	EX9204 Junos OS 12.3R2	EX9208 Junos OS 12.3R2
		EX9214 Junos OS 12.3R2	
		EX9214 Junos OS 12.3R2	

Name	Description	Platforms and Introduced Releases	
EX9200-40XS	A line card with 40 10-Gigabit Ethernet ports with Media Access Control Security (MACsec) capability, each of which can house 10-gigabit small form-factor pluggable plus (SFP+) transceivers	EX9204 Junos OS 12.3R2 EX9214 Junos OS 12.3R2	EX9208 Junos OS 12.3R2
EX9200-6QS	A line card with six 40-Gigabit Ethernet ports and 24 10-Gigabit Ethernet ports	EX9204 Junos OS 12.3R2 EX9214 Junos OS 12.3R2	EX9208 Junos OS 12.3R2
MX304-LMIC16	The MX304-LMIC16-BASE is a 16-port line card that supports maximum data throughput of 1.6 TB ingress and 1.6 TB egress	MX304 Junos OS 22.2R1	
PTX10K-LC1101	30x100G/30x40G Line Card	PTX10008 Junos OS 18.4R1	PTX10016 Junos OS 18.4R1
PTX10K-LC1102	36X40G/12X100G Line Card	PTX10008 Junos OS 18.4R1	PTX10016 Junos OS 18.4R1
QFX10000-60S-6Q	QFX10000 60-port 1/10G SFP/SFP+ line card with 6 40G QSFP+ / 2 100G QSFP28 ports	PTX10008 Junos OS 19.1R1 QFX10008 Junos OS 17.1R1	PTX10016 Junos OS 19.1R1 QFX10016 Junos OS 17.1R1

Modular Interface Cards (MICs)

Name	Description	Platforms and Introduced Releases	
10 Gigabit Ethernet			
EX9200-10XS-MIC	EX9200 MIC, 10-port 10GbaseX (Half-slot)	EX9204 Junos OS 12.3R2 EX9214 Junos OS 12.3R2	EX9208 Junos OS 12.3R2

Name	Description	Platforms and Introduced Releases	
SRX-MIC-10XG-SFPP	MIC with ten SFP+ 10-Gigabit Ethernet ports	SRX5400 Junos OS 12.3X48-D10	SRX5600 Junos OS 12.3X48-D10
		SRX5800 Junos OS 12.3X48-D10	

Modular Port Concentrators (MPCs)

Name	Description	Platforms and Introduced Releases	
10 Gigabit Ethernet			
MPC3E-3D-NG	MPC3E-3D-NG with port based queuing and flexible queuing option, Price includes full scale L2/L2.5 and reduced scale L3 features, Optics sold separately	MX240 Junos OS 12.3R1	MX480 Junos OS 12.3R1
		MX960 Junos OS 12.3R1	
MPC3E-3D-NG-Q	MPC3E-3D-NG-Q with full scale HQoS, Price includes full scale L2/L2.5 and reduced scale L3 features, Optics sold separately	MX240 Junos OS 12.3R1	MX480 Junos OS 12.3R1
		MX960 Junos OS 12.3R1	
MPC7E-10G	MPC7E 10G	MX240 Junos OS 16.1R7	MX480 Junos OS 16.1R7
		MX960 Junos OS 16.1R7	
MX-MPC3E-3D	MPC3E	MX240 Junos OS 12.3R1	MX480 Junos OS 12.3R1
		MX960 Junos OS 12.3R1	
MX-MPC3E-3D-NG	MPC3E NG	MX240 Junos OS 12.3R1	MX480 Junos OS 12.3R1
		MX960 Junos OS 12.3R1	

Name	Description	Platforms and Introduced Releases	
SRX5K-MPC3-100G10G	Fixed-configuration MPC with two 100-Gigabit Ethernet ports and four 10-Gigabit Ethernet ports	SRX5400 Junos OS 15.1X49-D10	SRX5600 Junos OS 15.1X49-D10
SRX5K-MPC3-40G10G	Fixed-configuration MPC with six 40-Gigabit Ethernet ports and twenty-four 10-Gigabit Ethernet ports	SRX5400 Junos OS 15.1X49-D10	SRX5600 Junos OS 15.1X49-D10
		SRX5800 Junos OS 15.1X49-D10	

Network Processing Cards (NPCs)

Name	Description	Platforms and Introduced Releases	
10 Gigabit Ethernet			
SRX1K3K-NP-2XGE-SFPP	2-port Ethernet SFP+ NP-IOC for SRX3400, SRX3600, and SRX1400 Services Gateways	SRX1400 Junos OS 12.1X44-D10	SRX3400 Junos OS 12.1X44-D10
		SRX3600 Junos OS 12.1X44-D10	

Services Processing Cards (SPCs)

Name	Description	Platforms and Introduced Releases	
10 Gigabit Ethernet			
SRX5K-SPC3	SRX5K-SPC3 Services Processing Cards (SPC) provide additional processing power to run integrated services such as firewall, IPSec, and IDP. The SRX5K-SPC3 contains two Services Processing Units (SPUs) with 128GB of memory per SPU.	SRX5400 Junos OS 12.3X48-D10	SRX5600 Junos OS 12.3X48-D10
		SRX5800 Junos OS 12.3X48-D10	

Uplink Modules

Name	Description	Platforms and Introduced Releases	
10 Gigabit Ethernet			
EX-UM-4SFPP-MR	EX4300, 4-Port 10G SFP+/4-Port 1G SFP Uplink Module	EX4300 Junos OS 18.2R1	EX4300 Multigigabit Junos OS 18.2R1
EX-UM-4X4SFP	EX4300, 4-Port 10G SFP+/4-Port 1G SFP Uplink Module	EX4300 Junos OS 13.2X50-D10	
EX-UM-8X8SFP	EX4300, 8-Port 10G SFP+/ 8-Port 1G SFP Uplink Module	EX4300 Junos OS 13.2X51-D15	
EX4400-EM-4S	4x10G SFP+ extension module for EX4400 series of switches	EX4400 Junos OS 21.1R1 EX4400-24T Junos OS 21.1R1 EX4400-24X Junos OS 23.1R1	EX4400-48T Junos OS 21.1R1 EX4400 Multigigabit Junos OS 21.2R1 EX4400-48F Junos OS 21.1R1
EX4400-EM-4Y	4x25G SFP28 extension module for EX4400 series of switches. MACsec AES256	EX4400 Junos OS 21.1R1 EX4400-24T Junos OS 21.1R1 EX4400-48F Junos OS 21.1R1	EX4400-48T Junos OS 21.1R1 EX4400 Multigigabit Junos OS 21.2R1

Why buy optics from Juniper?

There is value in choosing Juniper over 3rd party optics

✓ Full testing, validation, and JTAC support for Juniper optics

- Power, Electrical, and Management interfaces tested at the system level.
- Extended temperature and functional testing in DVT chamber using fully loaded systems.
- Full software integration into JUNOS/EVO for seamless part recognition, functionality, and telemetry.
- Latest qualification status and optics specifications published on [Hardware Compatibility Tool](#).

✓ Single-source provider for 1G to 400G on a variety of optical technologies

- Juniper's optics portfolio is maintained and constantly refreshed based on vendor availability.
- Automatic supply chain diversity and supply continuity - multiple optics suppliers fulfilled through Juniper.

✓ Rigorous evaluation of optical vendors

- Juniper ensures uniformity across all vendors by standardizing P-Specs for management, specs, and logs.
- Vendors are scored based on engineering and supply-chain analysis.
- Factory audits and critical component evaluation (Ex. Who is supplying the laser?).

Aren't 3rd party optics the same?

Optics may be a commodity, but some things are too good to be true

× Juniper does not Provide JTAC support for 3rd party optics

- JTAC will only assist with host-related issues unrelated to the use of 3rd party optics.

× Not all optics are the same - standards compliance does not guarantee quality or performance

- Third-party providers lack system-level knowledge and testing.
- No guarantee of vendor reliability or accountability.

× Newer technologies (ex. Coherent 400G ZR/ZR+) are complex and not simply plug-and-play

- Significant software integration necessary to enable full functionality, management, and telemetry.
- Use of unqualified 3rd party high-power optics can damage the host equipment.

× Third-party providers simply can't scale

- Incomplete solution offerings and fast turnaround times only for limited quantities.

Copyright © 2024, Juniper Networks, Inc. All rights reserved.

By accessing information contained in this document, you agree that:

- the information you are accessing is confidential to Juniper Networks
- you will not disclose this information to any party outside Juniper Networks
- you are authorized by Juniper Networks to access the information

The information in this document is provided "AS IS", with no warranties of any kind attached to the information. Any reliance upon the information shall be at the user's own risk. Juniper assumes no liability for the information contained in this document.